PATENT SPECIFICATION

(11)

1 340 503

NO DRAWINGS

(21) Application No. 22826/70

(22) Filed 12 May 1970

(23) Complete Specification filed 4 May 1971

(44) Complete Specification published 12 Dec. 1973

(51) International Classification COSF 29/16

(52) Index at acceptance

C3P 10C4A 10C8C 10D4A 10T1X

(72) Inventors TERENCE MICHAEL CADLE. LESLIE DAVID MANTON and. JOHN PETER MARRIOTT



(54) PLASTIC MATERIALS AND METHODS OF FABRICATING THEM

We, BRICO ENGINEERING LIMITED, a British Company, of Holbrook Lane. Coventry, Warwickshire, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—
This invention relates to processes for

10 fabricating plastics materials.

According to the invention there is provided a manufacturing process comprising compacting a mixture of polyretrafluoroethylene powder and carbon powder, and 15 subjecting the compacted mixture to micro-

wave radiation until a cohesive product is formed. The carbon powder powdered graphite or coke flour. can be

One example of the invention will now 20 be described. Polytetrafluorethylene powder of 400 micron particle size was mixed with Bavarian Carbon powder of 200 micron size in a laboratory analytical mill, in the

proportions of 80 per cent P.T.F.E. to 20 25 per cent carbon by volume. Whe mixture was then pressed into flat discs at room temperature at 5 tons/square inch by methods which are conventional in the P.T.F.E. processing art.

Discs were then placed in a microwave energy field of 2450 MHz frequency for 10 minutes; when examined it was found that the discs were fully sintered and had accept-

able mechanical properties.

As much as 50% or as little as 1% by volume of the P.T.F.E. may be replaced by the carbon.

In the example of the invention described above it has been found that approximately 16 lbs. of the mixture per hour could be heated to sintering temperature, using a microwave power of 0.4 kw.

It has also been found possible to add a further constituent to the material, such as glass fibre and still obtain acceptable mech- 45

anical properties.

WHAT WE CLAIM IS:-

1. A manufacturing process comprising compacting a mixture of polytetrafluoroethylene powder and carbon powder, and subjecting the compacted mixture to microwave radiation until a cohesive product is formed.

2. A process according to claim 1, wherein the carbon powder is powdered graphite

or coke flour.

3. A process according to either of the preceding claims wherein the mixture contains approximately 80% by volume of polytotrafluoroethylene powder and approximately 20% by volume of carbon powder.

4. A process according to claim I substantially as herein described with reference

to the Example.

5. A cohesive product when manufactured by a process in accordance with any of the preceding claims.

> MATHISEN & MACARA. Chartered Patent Agents. Lyon House, Lyon Road, Harrow, Middlesex, HA1 2ET. Agents for the Applicants.

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon), Ltd.—1973.

Published at The Patent Office' 25 Southan ton Buildings, London, WCZA 1AY, from which copies may be obtained.